





COLDWAVE

STAY COOL. STAY REFRESHED.







Features

- No Frost Evaporator
- Inner Cabinet with ABS Plastic
- Tropicalised for high ambient temperature
- Reciprocating Compressor
- Robust construction for heavy duty use
- Wheels for easy movement
- Double Layered Glass
- Sleek Decorative Look

Technical Specifications

Description	CWSC300I	CWSC400I	CWSC650I	CWSC1050I
Doors	Single	Single	Double	Three
Gross Capacity (Ltrs)	300	400	650	1050
Temp Range (°C)	+2°C to +8°C	+2°C to +8°C	+2°C to +8°C	+2°C to +8°C
No of Shelves	4 (Coated Wires)	4 (Coated Wires)	4 (Coated Wires)	4 (Coated Wires)
Inner Cabinet	ABS Plastic	ABS Plastic	Precoated Sheet	Precoated Sheet
Handle	Recessed	Recessed	Hand Gripped	Hand Gripped
Wheels	Yes - Front with Lock			
Type of Door	Double Layer Glass with Vaccum			
Color	White	White	Black	Black
Refrigerant	R-134A	R-134A	R-134A	R-290
Voltage/Frequency/Phase	230V/50Hz/SINGLE	230V/50Hz/SINGLE	230V/50Hz/SINGLE	230V/50Hz/SINGLE
Length (mm)	545	600	1060	1560
Depth (mm)	620	665	630	630
Height (mm)	1727	1877	2030	2050
Net Weight (Kg)	63	72	110	160



Administrative Office: COLDWAVE &&R PVT. LTD.

4 & 6, Kanha Estate, Sarkhej Fatewadi-Dholka Road, Nr. VIZAG Steel Wherehouse & Bharti Ashram, Ahmedabad 382210, Gujarat, INDIA.

Email: solutions@coldwave.in | Website: www.coldwave.in

Help Line: +91 93289 15888